

6EV5

Sharp-Cutoff Tetrode

7-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	6.3 \pm 10%	volts
Current at 6.3 volts.	0.2	amp

Direct Interelectrode Capacitances: ^a

Grid No.1 to plate.	0.035 max.	μ f
Grid No.1 to cathode & internal shield, grid No.2, and heater	4.50	μ f
Plate to cathode & internal shield, grid No.2, and heater	2.90	μ f


Characteristics, Class A₁ Amplifier:

Plate Voltage	250	volts
Grid-No.2 Voltage	80	volts
Grid-No.1 Voltage	-1	volt
Plate Resistance (Approx.)	0.15	megohm
Transconductance.	8800	μ hos
Plate Current	11.5	ma
Grid-No.2 Current	0.9	ma
Grid-No.1 Voltage (Approx.) for transconductance (μ hos) = 100.	-4.5	volts

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-1/8"
Maximum Seated Length	1-7/8"
Length, Base Seat to Bulb Top (Excluding tip)	1-1/2" \pm 3/32"
Diameter.	0.650" to 0.750"
Dimensional Outline	See <i>General Section</i>
Bulb.	T5-1/2
Base.	Small-Button Miniature 7-Pin (JEDEC No.E7-1)
Basing Designation for BOTTOM VIEW.	7EW

Pin 1-Grid No.1
Pin 2-Cathode,
Internal
Shield
Pin 3-Heater
Pin 4-Heater



Pin 5-Plate
Pin 6-Grid No.2
Pin 7-Cathode,
Internal
Shield

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE.	275 max.	volts
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE	180 max.	volts
GRID-No.2 VOLTAGE.	See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	



RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA
7-61

6EV5

GRID-No.1 (CONTROL-GRID) VOLTAGE:

Positive-bias value. 0 max. volts
CATHODE CURRENT. 20 max. ma

GRID-No.2 INPUT:

For grid-No.2 voltages up to 90 volts. . 0.2 max. watt

For grid-No.2 voltages between 90 and

180 volts. See *Grid-No.2 Input Rating Chart*
at front of Receiving Tube Section

PLATE DISSIPATION. 3.25 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode. 100 max. volts

Heater positive with respect to cathode. 100^b max. volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance 0.5 max. megohm

^a With external shield JEDEC No.316 connected to cathode.

^b The dc component must not exceed 50 volts.

